



ULTIMO PAPER

180 g/m²

Material Description Matt heavy graphic paper, Inkjet receptive coating on a barrier coated base paper, on the reverse side anti stress coated for perfect transport in the printer.

Printing with heavy ink loads are now possible without cockling of the paper. This alternative photo paper is a rigid quality what can be easily laminated.

Qualifications No cockling ~~no~~ barrier coating+ Good lamination characteristics (hot and cold)
Bright paper with a matt surface
Quick drying
Smudge and scratch proof
High water resistance
Brilliant colours and excellent sharp edges

Details Suitable for outdoor displays printed with UV pigmented ink*. 12 months behind glass without lamination; fade and smudge proof under normal conditions (shop window commercial), and 20 years in office environment. This expectation is dependent on the wide variety of conditions. Moisture resistant, lamination recommended.

Applications Indoor and outdoor posters (laminated)
Photos
Presentations
Tradeshows
Stands

Physical Properties	Quality	Barrier coated paper	
	Material	Matt Micropore Inkjet treated paper	
	Thickness	0.23 mm	
	Weight	180 g/m ²	
	Print side	Matt white	
	Reverse side	Anti stress coating.	

Compatibility

<p>Hewlett Packard Canon Epson And more</p>	<p>Eco Solvent Solvent Latex UV-curable UV-curable Led Water Oil Dye-sublimation</p>
---	---

Make your own practical test to be sure it reaches your quality standard. For all- and latest information see our Compatibility List.

Printing guidelines Max. temperature (material) should not exceed 80°C as overheating can impair the flatness of the media. Ink restrictions and heater settings have to be set for specific printer ink combinations to obtain the best results.

Colour profiles AT graphix develops high quality ICC colour profiles for the divers printing media's. We work with specialists that can do this service for almost every printer - rip combination.

Storage conditions 1 year under normal conditions (10. 25°C at a relative humidity of 30. 75 %). Higher humidity and/or temperature can affect the product performance. Always store the media in a dark place.

Environment The media and final prints can be disposed of as paper waste. Material is suitable for recycling. Please consult local recycle resources. For treatment of ink or ink residue, please refer to your printer manual or supplier.

Data presented in this product information serve only as a guide-line for compatibility and use. AT graphix will assume no liability in connection with any use of this information. Technical specifications are subjected to change without prior notice. AT graphix Vianen, The Netherlands. www.atgraphix.com